

iC-LV BLCC LV4C


OPTO ENCODER PACKAGE SPECIFICATION



Rev A5, Page 1/4

ORDERING INFORMATION

Type	Package	Options	Order Designation
iC-LV	BLCC LV4C		iC-LV BLCC LV4C




7.0 mm x 7.0 mm
RoHS compliant

PIN CONFIGURATION

PIN FUNCTIONS

(top view)



No.	Name	Function
1	LED	LED Power Control Output (high-side current source)
2	GND	Ground
3	SOUT	Serial Data Output (SSI) / Data Output D4
4	SERIN	Serial Data Input (SSI) / Data Output D3
5	SCLK	Clock Input (SSI) / Data Output D2
6	SYNM0	Synchronisation Mode Input / Data Output D1
7	SYNM1	Synchronisation Mode Input / Data Output D0
8	SEEN	Serial Error Bit Enable Input (high active)
9	n.c.	not connected
10	VCC	+4...+5.5 V Supply Voltage
11	NINV	Bit-wise Inversion Input (low active)
12	MODE	Operating Mode Selection Input
13	TEST	Test Mode Enable Input (high active)
14	RSET	LED Power Control Adjustment (wiring is optional)
15	NERR	Error Output (low active)
16	NDIR	Reversal of Rotation Dir. Input (low active)

ABSOLUTE MAXIMUM RATINGS

Item	Symbol	Parameter	Conditions	Fig.				Unit
					Min.	Typ.	Max.	
TG1	Ta	Operating Ambient Temperature Range			-40		125	°C
TG2	Ts	Storage Temperature Range			-40		125	°C
TG3	Tpk	Reflow Soldering Peak Temperature	tpk < 20 s, convection reflow				260	°C
			tpk < 20 s, vapour phase				230	
			TOL (time on label) 8 h; please refer to customer information file No. 7 for details					


iC-LV BLCC LV4C

OPTO ENCODER PACKAGE SPECIFICATION



Rev A5, Page 2/4

PHYSICAL DIMENSIONS



DRB_LV4C_ROT180_PACK_1

iC-LV BLCC LV4C

OPTO ENCODER PACKAGE SPECIFICATION



Rev A5, Page 3/4

DIMENSION TABLE

Item	Parameter	Comments					Unit
			Min.	Typ.	Max.	Tolerance	
	Substrate						
A1	Outline X			7.0		±0.2	mm
A2	Outline Y			7.0		±0.1	mm
A3	Alignment Hole Diameter	alignment hole center is reference		0.8		+0.05	mm
A4	Cut-Out Radius			1.0			mm
A5	Cut-Out Centers			1.0			mm
A6	Hole to Hole Pitch	tolerance applies also to Y-direction		4.0		±0.08	mm
A7	Outline vs. Reference Y			6.2		±0.15	mm
A8	Reference vs. Center Y			2.7		±0.15	mm
A9	Substrate Thickness	bottom package to bottom die	0.75	0.80	1.00		mm
	Encapsulation						
C1	Mold Thickness	note ¹⁾	0.50		0.70		mm
	Chip Placement						
G1	Chip Thickness			0.30			mm
H1	Chip Position vs. Reference Y	center of photodiode		5.44		±0.15	mm
H2	Chip Symmetry				0.4		mm
H3	Chip Parallelism				0.1		mm
	Bottom Metal Pattern						
J1	Lead Size			0.8		±0.15	mm
J2	Lead Pitch (or Lead-Lead Distance)	not accumulative		0.8		±0.08	mm
J3	Lead-Lead Spacing			0.15		±0.05	mm
J4	Lead Size			0.65		±0.05	mm
	Glass Cover						
L1	Glass Size X			0.95		±0.05	mm
L2	Glass Size Y			3.40		±0.05	mm
L3	Glass Position vs. Reference Y			5.55			mm
L4	Glass Thickness			0.40			mm
	Thickness Specifications						
T1	Overall Thickness	note ¹⁾ bottom substrate to top of glass	1.38		1.80		mm

Notes: ¹⁾ nominal glass thickness of 0.4 mm

iC-LV BLCC LV4C

OPTO ENCODER PACKAGE SPECIFICATION



Rev A5, Page 4/4

REVISION HISTORY

Rev	Notes	Pages affected
A1	Initial version	
A2	Table Pin Functions corrected	1
A3	Revision of pin layout (pad RC not connected)	1
A4	Revision of Absolute Maximum Ratings (TG3) Reflow Soldering; Physical Dimensions, Dimension Table Item H3 added; Minor changes	1, 2, 3

GENERAL HANDLING INSTRUCTIONS

After opening the dry pack, devices must be mounted within 8 hours (in factory conditions of maximum 30°C / 60% RH) or must be stored at <10% RH. Devices require baking before mounting if the Humidity Indicator Card shows >10% when read at 23°C ±5°C or if the conditions mentioned above are not met. Devices may be baked for 72 hours at 100°C using high-temperature device containers (trays).

Samples

Samples may not be subject for dry pack delivery, and, in that case, are not intended for reflow soldering.

This specification is for a newly developed product. iC-Haus therefore reserves the right to change or update, without notice, any information contained herein, design and specification; and to discontinue or limit production or distribution of any product versions. Please contact iC-Haus to ascertain the current data. Copying – even as an excerpt – is only permitted with iC-Haus approval in writing and precise reference to source.

iC-Haus does not warrant the accuracy, completeness or timeliness of the specification on this site and does not assume liability for any errors or omissions in the materials. The data specified is intended solely for the purpose of product description. No representations or warranties, either express or implied, of merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to information/specification or the products to which information refers and no guarantee with respect to compliance to the intended use is given. In particular, this also applies to the stated possible applications or areas of applications of the product.

iC-Haus conveys no patent, copyright, mask work right or other trade mark right to this product. iC-Haus assumes no liability for any patent and/or other trade mark rights of a third party resulting from processing or handling of the product and/or any other use of the product.

As a general rule our developments, IPs, principle circuitry and range of Integrated Circuits are suitable and specifically designed for appropriate use in technical applications, such as in devices, systems and any kind of technical equipment, in so far as they do not infringe existing patent rights. In principle the range of use is limitless in a technical sense and refers to the products listed in the inventory of goods compiled for the 2007 export trade statistics issued by the Bureau of Statistics in Wiesbaden in December 2006, for example, or to any product in the product catalogue published for the 2007 exhibition in Hanover (Hannover-Messe).

We understand suitable application of our published designs to be state-of-the-art technology which can no longer be classed as inventive under the stipulations of patent law. Our explicit application notes are to be treated only as mere examples of the many possible and extremely advantageous uses our products can be put to.